



2B, 2T & 3T-Series Timers

Models Available

2B Octal 8 Pin Timer (2 Pole)

2T 11 Pin Timer (2 Pole)

3T 11 Pin Timer (3 Pole)

Product Features


- Time ranges from 1 second to 60 hours
- Supply voltages from 12Vdc to 240Vac
- Octal 8 pin or 11 pin output
- Black 48mm square enclosure
- Local or remote potentiometer options
- Fixed time range option
- Plug-in socket mounting
- Plug-in sockets also available

The Tempatron 2B-series, 2T-series and 3T-series timers are housed in a compact 48mm square black enclosure which can surface/DIN rail mount to a socket and are powered from a large choice of AC or DC power options. Time ranges from 1 second to 60 hours are available, adjustable through the calibrated front control knob, or these timers can be supplied for use with a remote potentiometer. Fixed time ranges can also be specified.

These timers offer many different timing functions together with accurate, long-term switching reliability and high current switching contacts. The double pole or 3 pole changeover relay output contacts are isolated from the supply voltage and all timers (except TDD timers) have two LEDs to indicate both power and relay status.


For timing control of machinery, systems and operational processes

Dimensions




All dimensions in mm

Connections



2TDDP: SW across terminals 2 to 11
2TDDN: SW across terminals 10 to 11



View on pins

Ordering information

Model	Code	Description
	2B	Octal 8 Pin Timer (2 Pole)
	2T	11 Pin Timer (2 Pole)
	3T	11 Pin Timer (3 Pole)

Timing Function	Code	Description
	DE	Delay on Energise
	DDP	Delay on De-Energise - Positive Enabled (2T only)
	DDN	Delay on De-Energise - Negative Enabled (2T only)
	INT	Interval
	TDD	True Delay on De-Energise (N/A for 3T)
	DC	Delayed Cycling (N/A for 3T)
	IC	Immediate Cycling (N/A for 3T)

Time Range (Twice for DC or IC Function)	Code	Description
	1S	0.05 to 1 second
	2S	0.1 to 2 seconds
	5S	0.25 to 5 seconds
	10S	0.5 to 10 seconds
	30S	1.5 to 30 seconds
	60S	3 to 60 seconds
	2M	0.1 to 2 minutes
	5M	0.25 to 5 minutes
	10M	0.5 to 10 minutes
	30M	1.5 to 30 minutes
	60M	3 to 60 minutes (N/A for DD & TDD)
	2H	0.1 to 2 hours (N/A for DD & TDD)
	5H	0.25 to 5 hours (N/A for DD & TDD)
	10H	0.5 to 10 hours (N/A for DD & TDD)
	30H	1.5 to 30 hours (N/A for DD & TDD)
	60H	3 to 60 hours (N/A for DD & TDD)

Potentiometer (Twice for DC or IC Function)	Code	Description
	LP	Local Potentiometer
	RP	Remote Potentiometer (N/A for 3T)
	FT	Factory Preset Fixed Time Range (specify)

Auxiliary Power	Code	Description
	12VDC	12Vdc (N/A for TDD)
	24VDC	24Vdc
	110VAC	110Vac
	240VAC	240Vac
	Other	Specify (subject to technical viability)

Options	Code	Description
	AZ68	Octal DIN Rail/Panel Mount Socket
	AZ611	11 Pin DIN Rail/Panel Mount Socket
	S8P	Octal DIN Rail/Panel Mount Socket
	S11P	11 Pin DIN Rail/Panel Mount Socket

Example **2BDE10SLP230VAC**

Specification**Repeat Accuracy:**

- $\pm 1\%$ at constant ambient (20ms min.)
- Setting accuracy $\pm 5\%$

Power Supply Voltage:

- 24V, 50V, 110V, 240Vac ($\pm 15\%$)
- 12V, 24V, 48V, 100Vdc ($\pm 15\%$)

Minimum Supply Time (TDD only):

- (Tm+50)ms
where Tm = full range in seconds
(minimum 3 seconds)

Burden:

- 2W or 4VA (20VA for TDD)

Frequency:

- 50/60Hz

Relay Output:

- 2 or 3 pole changeover contacts

Contact Rating:

- 10A at 240Vac/30Vdc (resistive)
- TDD: 5A at 240Vac/30Vdc (resistive)

Electrical Contact Life:

- 500,000 operations at 10A
- 200,000 operations at 5A (TDD)

Mechanical Contact Life:

- 50 million operations at 10A
- 10 million operations at 5A (TDD)

Reset Time:

- 100ms approx. (200ms for DC)

Operating Temperature:

- -10°C to 60°C

Enclosure Code:

- Case IP40

Weight:

- 130g (TDD 150g)

Markings:

- CE marked (meets EN61010-1 low voltage and EN50081-1/50082-1 EMC directives)

Specification subject to change without notice.

Tempatron: Eltime House, Hall Road, Maldon, Essex, CM9 4NF UK.

TEMPATRON

Tempatron Industrial Controls is a division of Eltime Ltd.

© Eltime Ltd. Tempatron 2B, 2T & 3T-Series Timers 04/2016